



REVISION RECORD				
REV.	DESCRIPTION	ECN No.	APPROVED	DATE

IEC 技术参数 IEC Technical Data		IEC61076-2-101
工作温度 Operating temperatur [°C]	-25~+80	
防护等级 IP Class (IN Locked condition)	IP67	
额定电压 Rated Voltage [V]	60	
额定电流 Rated Current [A]	4	
导线截面积 Conductor cross section 硬质/柔性导线 Solid/ flexible [mm²]	0.34	
接线范围 Wire Range 单/多芯线 Solid/Stranded [AWG]	22	
材料 Material		
绝缘材料 Insulation Material	PA 66	
阻燃等级 Imflammability	UL94V-0	
导体材料 Contactor Material	铜合金 Copper alloy	
导体镀层 Contactive Coating	镀金 Gold Plated	
螺母/螺丝 Connector Nut/Screw	Brass With Nickel Plated 铜镀镍	
符合RoHS环保要求		

Contacts Pin 数	5Pin
A-Coding	
Rated Current 额定电流	4A
Rated Voltage 额定电压	250V
Wire Range 线范围	22AWG
PART NO. 品名: (1M)	M12-A05P-ST2-M02-BCC-100N
PART NO. 品名: (2M)	M12-A05P-ST2-M02-BCC-200N
PART NO. 品名: (3M)	M12-A05P-ST2-M02-BCC-300N
PART NO. 品名: (5M)	M12-A05P-ST2-M02-BCC-500N
Customized. 定制化	.....

P1	Wirelist
1	brown
2	white
3	blue
4	black
5	grey
Shield	Braid

编号 No.	料号 Materials No.	品名 Name	材料规格 Description	单位 Unit	用量 Qty
F		Pipe	Shield Pipe, Brass With Nickel Plated	pcs	1
E		TPU	Molded With Black TPU	G	8
D		Housing	A-Coding Male 5PIN, Black PA66	pcs	1
C		Terminal	Male Terminal, Brass With Gold Plated	pcs	5
B		Screw	Screw M12 X1.0, Brass With Nickel Plated	pcs	1
A		Cable	UL TYPE 22AWG X5C+AL+Braid Black PVC Jacket	mm	L

NO SPECIFIED TOLERANCE		Cus' P/IN:	Order No.:	---	Drawing No.:	SP-02-M00XXX
LINEAR	0.5-6	±0.1	DES.	JUN	DATE	UNITS mm
	6-30	±0.2	CHK.	DATE	SCALE	A4
	>30	±2%	APP.	DATE	SCALE	X:X
ANGLES	±1°		THIRD ANGLE PROJECTION		PAGE 1 of 1	
文件等级: 外部公开						



慈溪市万捷电子有限公司  
CIXI WANJIE ELECTRONIC CO., LTD

PART NO.:  
M12-A05P-ST2-M02-BCC-XXXN